

AMRA-201:2023(en)

2023-11-23

Mobile Robots General Requirements and Test Methods

(P.1 ~ P.8 preview with watermark)

NOTICE

This document is copyright protected.
© AMRA Autonomous Mobile Robot Alliance 2023

All rights reserved. Inquiries and comments relative to the contents of this document should be addressed to AMRA. Without prior written permission, no part of this document may be reproduced or utilized in any form, including posting on the internet or an intranet. AMRA retains the copyright on the material. By downloading this file, the individual agrees not to charge for or resell the resulting material.

For standard improvement, summit comments: https://forms.gle/nsMRGhvD7cmY3kfs5



INTRODUCTION

Mobile robots play the role of moving goods or products in various fields, for example, smart factories, warehouses and restaurants. AGV and AMR are the most popular mobile robot products in these applications. To shape a better ecosystem, AMRA develops industrial standards on the critical aspects about mobile robot products.

AMRA-201 provides guidance for mobile robot products regarding their general requirements and test methods, and one of its purposes is to align common understanding between manufacturers and users. Manufacturers can adopt it as the baseline of product specification. Users can evaluate the mobile robot products according to the same conditions. In AMRA, this standard is formed by the experts in working group #1 (WG1), reviewed by the technical committee and approved by the board. The participants in the following list, sorted alphabetically, make great contributions to this version of the standard. For a list of participants who contributed to the previous version of the standard, refer to AMRA-201:2021(en)-ED2.

Board

Approved AMRA-201:2023(en) on 2023-11-20

- ASUS
- AUO Corporation
- CASTEC International
- CiLS
- DEKRA iST Reliability Services
- Delta Electronics
- eYs3D Microelectronics
- ITRI [Chair]
- Wistron Corporation

Technical Committee

Reviewed AMRA-201:2023(en) on 2023-11-06

- Aerospace Industrial Development
 Corporation (AIDC)
- ASUS
- AUO Corporation

- DEKRA iST Reliability
 Services
- Delta Electronics
- ITRI [Chair]

- PMC
- Siliconware Precision Industries
 Ltd. (SPIL)
- TAC dynamics

Working Group #1 Experts

Formed the draft of AMRA-201:2023(en)

Chi-Chao Hsu Jack Lee Jennifer Chang [Chair] Jimmy Chow Josh Chang Ken Chen Nelson Chang Patrick Zheng [Co-chair]
Wei-Ming Chen

CONTENTS

SCOPE	•
NORMATIVE REFERENCES	ç
TERMS AND DEFINITIONS	10
3.1 Autonomous mobile robot (AMR)	10
3.2 Automated guided vehicle (AGV)	10
3.3 Collision stop (CS)	10
3.4 Obstacle avoidance (OA)	10
3.5 Carried load	10
3.6 Drag load	10
3.7 Fork load	10
3.8 Manipulator load	11
3.9 Manipulator reach	11
3. <mark>10 Transit</mark>	11
3 <mark>.11</mark> Po <mark>se</mark> accuracy	11
3.12 Docking repeatability	11
3.13 Repeatability	11
3.14 Absolute error	11
3.15 Navigation speed	11
3.16 Collision stop maximum speed	12
3.17 Obstacle avoidance average speed	12
3.18 Slope	12
3.19 Maximum slope climbing ability	12
3 <mark>.20 Empt</mark> y enclosure	12
3.21 Working footprint	12
	12
	12
	12
	12
	13
	14
	16
	16
·	16
·	16
	16
	16
	17
5.3 Locomotion method	17
	NORMATIVE REFERENCES TERMS AND DEFINITIONS 3.1 Autonomous mobile robot (AMR) 3.2 Automated guided vehicle (AGV) 3.3 Collision stop (CS) 3.4 Obstacle avoidance (OA) 3.5 Carried load 3.6 Drag load 3.7 Fork load 3.8 Manipulator load 3.9 Manipulator reach 3.10 Transit 3.11 Pose accuracy 3.12 Docking repeatability 3.13 Repeatability 3.14 Absolute error 3.15 Navigation speed 3.16 Collision stop maximum speed 3.17 Obstacle avoidance average speed 3.18 Slope 3.19 Maximum slope climbing ability 3.20 Empty enclosure

	5.3.1 Drive configuration type	17
	5.4 Emergency stop	17
	5.5 Controller type	17
	5.6 External communication interface	18
	5.7 Power supply	18
	5.7.1 Battery	18
	5.7.2 Charging interface	19
	5.8 Rated load	19
	5.9 Manipulator reach (Applied to mobile robot with manipulator only)	20
	5.10 Rated speed	20
	5.11 Maximum climbing ability	20
	5.12 Navigation	20
	5.1 <mark>2.1</mark> Navigation speed	20
	5.12.2 Pose accuracy	20
	5.12.3 Collision stop (CS) and obstacle avoidance (OA)	21
	5.12.4 Docking performance	21
	5.13 Long-term stability	21
	5.14 Particle	21
	5.15 Vibration	21
	5.16 Ingress protection code (IP code)	22
	5.17 Ability to change direction	22
	5.18 Seismic performance	22
6.	TEST METHODS	23
	6.1 Environmental conditions	23
	6.2 Scenarios	23
	6.3 Battery	29
	6.3.1 Battery running time test	29
	6.3.2 Battery charging time test	29
	6.4 Rated load test	30
	6.5 Manipulator reach test	31
	6.6 Rated speed test	32
	6.7 Maximum clim <mark>bing ability test</mark>	33
	6.8 Navigation	34
	6.8.1 Navigation speed test	34
	6.8.2 Pose accuracy	35
	6.8.2.1 Docking repeatability test	35
	6.8.2.2 Repeatability test	37
	6.8.2.3 Absolute error test	39
	6.8.3 Collision stop (CS) and obstacle avoidance (OA)	40
	6.8.3.1 Obstacle type	40

6.8.3.2 Collision stop (CS) test	42
6.8.3.3 Obstacle avoidance (OA) test	44
6.8.4 Docking performance test	47
6.9 Particle test	48
6.10 Vibration test	49
6.11 IP code test	50
6.12 Seismic performance test	50
ANNEX A. (INFORMATIVE) CHANGES BETWEEN VERSIONS	52
ANNEX B. (INFORMA <mark>TIVE) RECOMMENDED POSE MEASUREMENT APPROACHES</mark>	53



TABLES

<u>lable 1. Characteristics to be specified for mobile robots and charging stations</u>	.14
Table 2. Types of loads	19
Table 3. Summary of scenarios	24
Table 4. Table for the result of battery running time test	.29
Table 5. Table for the result of battery charging time test	30
Table 6. Table for the result of rated load test.	31
Table 7. Table for the result of manipulator reach test	.31
Table 8. Table for the result of rated speed test	.32
Table 9. Table for the result of maximum climbing ability test	33
Table 10. Ta <mark>ble for the result of navigation speed test</mark>	35
Table 11. Table for the result of docking repeatability test	.36
Table 1 <mark>2. T</mark> abl <mark>e fo</mark> r the result of repeatability test	.38
Table 13. Table for the result of absolute error test	.40
Table 14. Types of obstacles	.41
Tabl <mark>e 1</mark> 5. Relationship of the combinations of obstacle detection capability class an <mark>d d</mark> iffe <mark>re</mark> n	<u>1t</u>
<u>obs<mark>tacle type</mark></u>	.42
Ta <mark>ble</mark> 16. Table for the result of collision stop tests	.43
Table 17. Relationship of collision stop capability levels and tests of different scenario	
co <mark>mbinations</mark>	<mark>.4</mark> 4
Ta <mark>ble 18. T</mark> able for the result of obstacle avoidance test	46
Ta <mark>ble</mark> 19. Relationship of obstacle avoidance capability levels and tests of different sc <mark>en</mark> ario	
co <mark>mbinations</mark>	.46
Table 20. Table for the result of docking performance test	.48
Tabl <mark>e 21. Tab</mark> le for the result of particle test	49
Table 22. Table for the result of vibration test	50
Table 23. Table for the result of seismic performance test	51

FIGURES

Figure B.1. Mobile robot with a downward pointing laser pointer	53
Figure B.2. Example of a record sheet with position marks and average position	53
Figure B.3. Mobile robot with 2 downward pointing laser pointers and its orientation	54
Figure B.4. Example of a record sheet with orientation marks and average orientation	54
Figure B.5. Measuring position using a laser tracker and a reflecting lens.	55
Figure B.6. Measuring orientation using a laser tracker and two reflecting lenses	
Figure B.7. Example showing the coordinate transformation for the pose absolute error	56

